

### YB 系列技术参数

型号	额定功率		额定电压 (V)	额定电流 (A)	额定频率 (Hz)	转速 (r/min)
	(kW)	(HP)				
同步转速 3000r/min 2 极						
YB-801-2	0.75	1	380	1.8	50	2840
YB-802-2	1.1	1.5	380	2.6	50	2840
YB-90S-2	1.5	2	380	3.4	50	2850
YB-90L-2	2.2	3	380	4.8	50	2850
YB-100L-2	3	4	380	6.2	50	2870
YB-112M-2	4	5.5	380/660	8.1/4.7	50	2890
YB-132S1-2	5.5	7.5	380/660	11.1/6.3	50	2900
YB-132S2-1	7.5	10	380/660	14.8/8.6	50	2900
YB-160M1-2	11	15	380/660	21.6/12.5	50	2940
YB-160M2-1	15	20	380/660	28.8/16.6	50	2940
YB-160L-2	18.5	25	380/660	35.5/20.5	50	2940
YB-180M-2	22	30	380/660	41/23.7	50	2950
YB-200L1-2	30	40	380/660	55.5/32.1	50	2950
YB-200L2-2	37	50	380/660	67.9/39.2	50	2950
YB-225M-2	45	60	380/660	82.1/47.4	50	2960
YB-250M-2	55	75	380/660	99.7/57.5	50	2970
YB-280S-2	75	100	380/660	134.4/77.5	50	2970
YB-280M-2	90	125	380/660	160.2/92.5	50	2970
YB-315S-2	110	154	380/660	195.4/112.5	50	2980
YB-315M-2	132	184	380/660	233.2/134.3	50	2980
YB-315L1-2	160	222	380/660	279.3/160.8	50	2980
YB-315L2-2	200	279	380/660	348.4/200.6	50	2980
同步转速 1500r/min 4 极						
YB-801-4	0.55	0.75	380	1.5	50	1390
YB-802-4	0.75	1	380	2	50	1390
YB-90S-4	1.1	1.5	380	2.9	50	1390
YB-90L-4	1.5	2	380	3.7	50	1390
YB-100L1-4	2.2	3	380	5.1	50	1420
YB-100L2-4	3	4	380	6.8	50	1420
YB-112M-4	4	5.5	380/660	8.8/5.1	50	1430
YB-132S-4	5.5	7.5	380/660	11.5/6.7	50	1440
YB-132M-4	7.5	10	380/660	15.4/8.9	50	1440
YB-160M-4	11	15	380/660	22.3/12.9	50	1460
YB-160L-4	15	20	380/660	30.1/17.4	50	1460
YB-180M-4	18.5	25	380/660	36.5/21.1	50	1470
YB-180L-4	22	30	380/660	43.1/24.9	50	1470

YB-200L-4	30	40	380/660	57.6/33.3	50	1470
YB-225S-4	37	50	380/660	69.9/40.3	50	1480
YB-225M-4	45	60	380/660	84.7/48.9	50	1480
YB-250M-4	55	75	380/660	102.7/59.3	50	1480
YB-280S-4	75	100	380/660	139.6/80.6	50	1480
YB-280M-4	90	125	380/660	166.9/96.3	50	1480
YB-315S-4	110	154	380/660	198.7/114.4	50	1485
YB-315M-4	132	184	380/660	237.7/136.9	50	1485
YB-315L1-4	160	222	380/660	284.3/163.7	50	1485
YB-315L2-4	200	279	380/660	354.7/204.2	50	1485
同步转速 1000r/min 6 极						
YB-801-6	0.37	0.5	380	1.3	50	890
YB-802-6	0.55	0.75	380	1.7	50	890
YB-90S-6	0.75	1	380	2.3	50	910
YB-90L-6	1.1	1.5	380	3.1	50	910
YB-100L-6	1.5	2	380	3.9	50	930
YB-112M-6	2.2	3	380	5.6	50	940
YB-132S1-6	3	4	380	7.3	50	970
YB-132S2-6	4	5.5	380/660	9.4/5.4	50	970
YB-160M1-6	5.5	7.5	380/660	12.6/7.2	50	970
YB-160M2-6	7.5	10	380/660	16.8/9.7	50	970
YB-160L-6	11	15	380/660	24.3/14	50	970
YB-180M-6	15	20	380/660	31.6/18.3	50	980
YB-200L1-6	18.5	25	380/660	37.6/21.7	50	980
YB-200L2-6	22	30	380/660	44.7/25.8	50	980
YB-225M-6	30	40	380/660	57.6/33.3	50	980
YB-250M-6	37	50	380/660	69.8/40.3	50	980
YB-280S-6	45	60	380/660	85.9/49.6	50	990
YB-280M-6	55	75	380/660	104.7/60.5	50	990
YB-315S-6	75	100	380/660	141.7/81.6	50	990
YB-315M-6	90	125	380/660	169.5/97.6	50	990
YB-315L1-6	110	154	380/660	206.7/119	50	990
YB-315L2-6	132	184	380/660	244.7/140.9	50	990
同步转速 750r/min 8 极						
YB-801-8	0.18	0.25	380	0.8	50	650
YB-802-8	0.25	0.34	380	1.1	50	650
YB-90S-8	0.37	0.5	380	1.4	50	670
YB-90L-8	0.55	0.75	380	2.1	50	670
YB-100L1-8	0.75	1	380	2.4	50	690
YB-100L2-8	1.1	1.5	380	3.3	50	690
YB-112M-8	1.5	2	380	4.4	50	690
YB-132S-8	2.2	3	380	5.6	50	710

YB-132M-8	3	4	380	7.6	50	710
YB-160M-8	4	5.5	380/660	10.3/5.9	50	720
YB-160L-8	5.5	7.5	380/660	13.4/7.8	50	720
YB-180M-8	7.5	10	380/660	17.5/10.1	50	720
YB-180L-8	11	15	380/660	25.3/14.6	50	730
YB-200L-8	15	20	380/660	33.7/19.5	50	730
YB-225S-8	18.5	25	380/660	40/23.1	50	740
YB-225M-8	22	30	380/660	47.4/27.3	50	740
YB-250M-8	30	40	380/660	63.4/36.6	50	740
YB-280S-8	37	50	380/660	77.8/44.9	50	740
YB-280M-8	45	60	380/660	94.1/54.3	50	740
YB-315S-8	55	75	380/660	111.2/64	50	740
YB-315M-8	75	100	380/660	151.3/87.1	50	740
YB-315L1-8	90	125	380/660	177.8/102.4	50	740
YB-315L2-8	110	154	380/660	216.8/124.8	50	740
同步转速 600r/min 10 极						
YB-315S-10	45	60	380/660	99.1/57.1	50	585
YB-315M-10	55	75	380/660	121.1/69.7	50	585
YB-315L1-10	75	100	380/660	162.1/93.3	50	585
YB-315L2-10	90	125	380/660	191/110	50	585